ABS

WELDING CONSUMABLE CERTIFICATE

Certificate No.: 848327-3629310-001	
Report No.: 5629310	
Port of KOBE, JAPAN	
Date: 2 MAY 2023	

THIS IS TO CERTIFY

THAT THE UNDERSIGNED SURVEYOR TO THIS BUREAU DID, AT THE REQUEST OF KOBE STEEL, LTD. FUKUCHIYAMA PLANT, JAPAN, ATTEND THEIR PLANT AT FUKUCHIYAMA & FUJIWSAWA, JAPAN, ON THE 17TH DAY OF JANUARY, 2023 AND ON SUBSEQUENT DATES, IN ORDER TO CARRY OUT A PLANT SURVEY OF FACILITIES AND ASSOCIATED QUALITY ASSURANCE AND QUALITY CONTROL PROCEDURES AND TO WITNESS AND REPORT ON THE ANNUAL APPROVAL TESTING OF WELDING CONSUMABLES; AND,

THAT THE FACILITY IS CONSIDERED CAPABLE OF PROVIDING AN ACCEPTABLE UNIFORM PRODUCT, AND THAT EACH WELDING CONSUMABLE LISTED BELOW WAS FOUND IN COMPLIANCE WITH THE SPECIFICATION INDICATED AND IS ELIGIBLE TO BE PLACED ON THIS BUREAU'S APPROVED WELDING CONSUMABLES LIST IN THE GAS METAL ARC WELDING INCLUDING MIG/TIG WELDING SECTION:

TRADE NAME	SPECIFICATION	OR CLASS	HIELDING GAS	<u>POSITION</u>	CURRENT/ POLARITY	SIZE
TG-S50	ABS	3, 3Y	Ar	All	DCEN	1.6-3.2mm
TG-S1N	ABS	4YSA**	Ar	All	DCEN	1.6-2.4
** Manufacturer's	s guaranteed minimum C	VN values of 47 J at min	us 60 Cen. De	eg.		
TG-S2CW	**	**	Ar	All, HF	DCEN	0.8-3.2
**Manufacturer's	guaranteed minimum pr	operties; Y.S. 530 N/mm	2, T.S. 620 N	mm2, El.16 %		
TG-S80AM	ABS	5YQ690SA, H5	Ar	All, HF	DCEN	1.2-2.4
MG-50	ABS	3SA, 3YSA	C1	F, H, V-Down	DCEP	1.2-1.4
		3SA, 3YSA	C1	F, H	DCEP	1.6
MG-50	ABS	3SA, 3YSA	M21	F, H	DCEP	1.2-1.6
MG-50T	ABS	3SA, 3YSA	C1	All, V-Down	DCEP	0.9-1.4
645		3SA, 3YSA	CĨ	F, H	DCEP	1.6
MG-50T	ABS	3SA, 3YSA	M21	All	DCEP	0.9-1.2
SE-50T	ABS	3SA, 3YSA	. C1	All, V-Down	DCEP	0.9-1.2
SE-A50S	ABS	3SA, 3YSA	M21	All	DCEP	1.2

TO BE CONTINUED

This Certificate evidences compliance with one or more of the Rules, guides, standards or other criteria of American Bureau of Shipping and is issued solely for the use of the Bureau, its committees, its clients or other authorized entities. This Certificate is a representation only that the structure, item of material, equipment, machinery or any other item covered by this Certificate has met one or more of the Rules, guides, standards or other criteria of American Bureau of Shipping as of the date of issue. Perfect any expected to review the Rules for the scope and conditions of classification and to review the survey records for a fuller description of any restrictions or limitation on the vessel's service or surveys. The validity, applicability and interpretation of this Certificate is governed by the Rules and standards of American Bureau of Shipping who shall remain the sole judge thereof. Nothing contained in this Certificate or in any notation made in contemplation of this Certificate shall be deemed to relieve any designer, builder, owner, manufacturer, seller, supplier, repairer, operator or other entity of any warranty express or implied.

Page 1 of 1

Note:

Certificate no.: 848327-5629310-002

Report No.: 5629310 Port of: Kobe, Japan Date: 2 May 2023

TRADE NAME	SPECIFICATION	GRADE OR CLASS	SHIELDING GAS	POSITION	CURRENT/ POLARITY	SIZE
MIX-50	ABS ABS	3SA, 3YSA 3SA, 3YSA	M21 M21	All F, H	DCEP DCEP	mm 0.9-1.2 1.4-1.6
MIX-50S	ABS ABS ABS	3SA, 3YSA 3SA, 3YSA 3SA, 3YSA	M21 M21 M21	All, V-Down F, H, V-Down F, H	DCEP DCEP DCEP	0.9-1.2 1.4 1.6
MG-S80	**	**	M21	F	DCEP	1.2-1.6

^{**}Manufacturer's guaranteed minimum properties; Y.S. 690 N/mm2, T.S. 780 N/mm2, El. 14 %, CVN 35 J at minus 40 Cen. Deg. And

Manufacturer's chemical composition of wire: C: 0.12 % max, Mn: 1.1-1.6 %, Si: 0.3-0.6 %, S: 0.03% max, P: 0.03% max, Ni: 2.4-3.0 %, Mo: 0.3-0.7 %, Cr: 0.1-0.4%

MG-S88A	ABS	4YQ690SA** H5	M21	All	DCEP	1.2
** Manufacturer's	s guaranteed minim	um CVN values of 47 J at minu	ıs 60 Cen.	Deg.		

MG-T1CM ** ** M21 All DCEP 1.2



This Certificate evidences compilance with one or more of the Rules, guides, standards or other criteria of American Bureau of Shipping and is issued solely for the use of the Bureau, its committees, its clients or other authorized entities. This Certificate is a representation only that the structure, item of material, equipment, machinery or any other item covered by this Certificate has met one or more of the Rules, guides, standards or other criteria of American Bureau of Shipping as of the date of issue. Parties are advised to review the Rules for the scope and conditions of classification and to review the survey records for a fuller description of any restrictions or limitation on the vessel's service or surveys. The validity, applicability and interpretation of this Certificate is governed by the Rules and standards of American Bureau of Shipping who shall remain the sole judge thereof. Nothing contained in this Certificate or in any notation made in contemplation of this Certificate shall be deemed to relieve any designer, builder, owner, manufacturer, seller, supplier, repairer, operator or other entity of any warranty express or implied.

Note:

^{**}Manufacturer's guaranteed minimum properties; Y.S. 460 N/mm2, T.S. 560 N/mm2, El.19 %, And Manufacturer's chemical composition of wire: C: 0.12 % max, Mn: 0.60-1.40 %, Si: 0.30-0.90 %, S: 0.025% max, P: 0.025 % max, Cu: 0.35 % max, Ni: 0.20 % max, Cr: 1.10-1.60 %, Mo: 0.4-0.65 %, Post weld heat treatment: 690 +/- 15 Cen. Deg. x 1Hr, For welding of 1/1.25% Cr-0.5% Mo Steels.